

MT1887 TRMS INDUSTRIAL MULTIMETER

OFF

REL

RANGE

uA

4.0

10A

mA

MAX

CAT IV 600V

COM

IEC

61010-1

CAT III

1000V

PEAK

HOLD

MT1887IS Intrinsically safe Industrial Multimeter

The MT1887IS is a CAT IV 600V True RMS professional multimeter having improved measurement functions, troubleshooting feature, resolution and accuracy to solve problems on power distribution, motor drives, electromechanical equipment and plant automation with the 4-20mA% loop measurements. The meter has a large 40 000 count backlit LCD with the added advantage of a 41 segment analogue bargraph. NCV function, automatic Non-Contact voltage detection, the LCD backlight will be in red when AC voltage above 110V is sensed. Specially designed for the Solar Industry the DC voltage range measures up to 1500V DC, other measuring ranges include ACV to 1000V, Micro Amps and Amps, Frequency, Resistance, Duty Cycle, capacitance and temperature measurements. The Bluetooth function allows the user to transmit data to the Android or iOS mobile App for viewing, organising and sharing recordings.

Features



- IEC EX Rating: Ex ib IIAT4 Gb
- Ex ib I Mb
- 40 000 count with 41 Segment Bargraph
- Measures DCV to 1500V & ACV up to 1000V
- Temperature measurement from -50°C to 1000°C
- AC & DC Micro Amps up to 10A
- 4-20mA process loop measurements with % reading
- Capacitance to 40 mF
- Frequency to 100MHz
- Duty Cycle
- Relative mode
- Automatic NCV where LCD backlight turns red
- Min, Max and Data Hold
- Auto Power Off



Range	Accuracy
400.0mV – 1500V	±(0.1% +6)
4.0000V - 1000V	±(1.0% +8)
400.0µA – 10A	±(1.0% +3)
600.0µA – 10A	±(1.5% +8)
$400.0\Omega - 40M\Omega$	±(0.5% +8)
40.000Hz - 99.99MHz	±(0.1% +1)
40.00nF – 40mF	±(2.5% +10)
50°C - 1000°C	±(1.0% +2.5°C)
25% to 125%	±50 dgt
0.01% to 95.0%	±(1.2% +2)
Ex ib IIAT4 Gb	
Ex ib I Mb	
87 x 81 x 50mm	
342gm	
	$\begin{array}{l} 400.0 \text{mV} - 1500\text{V} \\ 4.0000\text{V} - 1000\text{V} \\ 400.0 \mu\text{A} - 10\text{A} \\ 600.0 \mu\text{A} - 10\text{A} \\ 400.0 \Omega - 40\text{M}\Omega \\ 40.000\text{Hz} - 99.99\text{MHz} \\ 40.000\text{F} - 40\text{MF} \\ 50^{\circ}\text{C} - 1000^{\circ}\text{C} \\ 25\% \text{ to } 125\% \\ 0.01\% \text{ to } 95.0\% \\ \text{Ex ib IIAT4 Gb} \\ \text{Ex ib I Mb} \\ 87 \text{ x } 81 \text{ x } 50\text{mm} \end{array}$

REL MAX 40 000 Count Backlight Display





MT1887IS

IEC

61010-1

CAT IV

600V

Intrinsically safe Industrial Multimeter with Bluetooth 4.0

Contact Us South Africa

Australia

🌐 www.major-tech.com 🛛 🖂 sales@major-tech.com

🌐 www.majortech.com.au 🛛 🖂 info@majortech.com.au