



MT332 Earth Resistance Tester

The MT332 Earth Resistance Clamp meter is used to test earth resistance and leakage current in the loop and features a sleek black screen design. This device displays resistance current on the same screen, along with convenient functions such as data storage, data review, alarm, and automatic shutdown. With a wide measuring range and high resolution, the MT332 ensures accurate measurements. Built with a shock, dust and moisture proof structure, the MT332 is well-suited for demanding environments. Its user-friendly interface and convenient carry case make it a practical choice for various applications. The instrument is known for its stable performance and strong anti-interference ability. It is an essential tool in telecommunications, electricity, meteorology, computer rooms, oil fields, and electromechanical installation and maintenance within industrial enterprises utilizing electricity as power or energy source. Controlled by a microprocessor, the Clamp-On Earth Resistance Tester employs advanced fast filtering techniques to minimize interference, ensuring precise and reliable results. Additionally, it offers simultaneous data storage and upload functions for enhanced efficiency in testing procedures.



Features

- Earth resistance measurement
- Earth Resistance range from 0.001Ω to 1200Ω
- Current range from 0.01mA to 20A
- Displays resistance and current simultaneously
- Quick self-test function
- Fast filtering technology minimises strong interference
- Data storage of 300 sets
- Alarm when the measured value is greater that set alarm threshold
- NOISE symbol when earth loop under test has interference current
- Bluetooth function allows connection to mobile phones

Function	Range	Accuracy
Resistance	0.010Ω – 0.099Ω	±(1% +0.01Ω)
	0.01Ω – 0.09Ω	±(1% +0.01Ω)
	1.0Ω – 49.9Ω	±(1% +0.01Ω)
	50.0Ω – 99.5Ω	±(1.5% +0.5Ω)
	100Ω – 199Ω	±(2% +1Ω)
	200Ω – 395Ω	±(5% +5Ω)
	400Ω – 590Ω	±(10% +10Ω)
	600Ω – 880Ω	±(20% +20Ω)
	900Ω – 1200Ω	±(25% +30Ω)
Current	0.01mA – 9.95mA	±(2.5% +1mA)
	10.0mA – 99.0mA	±(2.5% +5mA)
	100mA – 3000mA	±(2.5% +10mA)
	0.30A – 2.99A	±(2.5% +0.1A)
	3.0A – 99.0mA	±(2.5% +0.3A)
Conductor size	55mm x 32mm	
Size	285 x 85 x 58mm	
Weight	1180g	



Black LCD that Simultaneously Displays Resistance & Current



55 x 32mm Large Jaw Size



Buttons for Easy Usage

MT332

Earth Resistance Tester

Contact Us
South Africa

Australia

www.major-tech.com

sales@major-tech.com

www.major-tech.com.au

info@major-tech.com.au